

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

BEST AVAILABLE COPY**AMENDMENTS TO THE CLAIMS**

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. (Currently Amended) A channel estimation device comprising:
weighting factor generating means for generating weighting factors for weighting and averaging pilot symbols, which are time multiplexed with a control channel, which is parallel multiplexed with a data channel; and

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols of said data channel,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claim 2. (Original) The channel estimation device as claimed in claim 1, wherein said weighting factor generating means generates weighting factors to be used for weighting and averaging mean values of the pilot symbols in a plurality of slots of said control channel, and said channel estimation value calculating means weights and averages the mean values of said pilot symbols using said weighting factors and calculates the channel estimation value of the data symbols of said data channel.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 3. (Cancelled).

Claim 4. (Previously Presented) The channel estimation device as claimed in claim 1, wherein said weighting factor generating means divides the data symbols in the slots of said data channel into a plurality of data symbol sections, selects the pilot symbols appropriate for calculating the channel estimation value of the data symbols in each of the data symbol sections, and generates the weighting factors to be used for weighting and averaging the pilot symbols; and said channel estimation value calculating means takes weighted average of said pilot symbols using said weighting factors and calculates the channel estimation value of the data symbols of each of the data symbol sections.

Claim 5. (Currently Amended) ~~[[The]] A channel estimation device as claimed in claim 4 comprising:~~

weighting factor generating means for generating weighting factors for weighting and averaging pilot symbols, which are time multiplexed with a control channel, which is parallel multiplexed with a data channel; and

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols of said data channel,

wherein said weighting factor generating means divides the data symbols in the slots of said data channel into a plurality of data symbol sections, selects the pilot symbols appropriate for calculating the channel estimation value of the data symbols in each of the data symbol

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

sections, and generates the weighting factors to be used for weighting and averaging the pilot symbols; and said channel estimation value calculating means takes weighted average of said pilot symbols using said weighting factors and calculates the channel estimation value of the data symbols of each of the data symbol sections.

wherein in order to calculate the channel estimation value of the data symbols of the last data symbol section of the i -th (i : integer) slot and to calculate the channel estimation value of the data symbols of the first data symbol section of the $(i+1)$ -th slot, said weighting factor generating means selects the same pilot symbol and generates the weighting factors to be used for weighting and averaging the pilot symbols.

Claim 6. (Currently Amended) The channel estimation device as claimed in ~~any~~ one of claims claim 1, further comprising:

fading frequency decision means for deciding the fading frequency based on an inner product value of said pilot symbols; and

factor altering means for altering the factors that are used in taking said weighted average according to the fading frequency decided by said fading frequency decision means.

Claim 7. (Currently Amended) The channel estimation device as claimed in ~~any~~ one of claims claim 1, wherein a transmission rate of said data channel differs from the transmission rate of said control channel.

Claim 8. (Currently Amended) A demodulation device comprising:

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

weighting factor generating means for generating weighting factors to be used for weighting and averaging pilot symbols being time multiplexed in a control channel that was parallel multiplexed together with a data channel;

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and for calculating a channel estimation value of data symbols of said data channel; and

channel variation compensating means for compensating channel variation of said data symbols using the channel estimation value calculated by said channel estimation value calculating means,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claims 9-17. (Cancelled).

Claim 18. (Currently Amended) A channel estimation device for calculating a channel estimation value of data symbols using pilot symbols in a channel in which said data symbols and said pilot symbols are time multiplexed, said channel estimation device comprising:

weighting factor generating means for dividing data symbols in a slot of said channel into a plurality of data symbol intervals, selecting pilot symbols suitable for calculation of a channel estimation value of data symbols during each data symbol interval and generating weighting factors for weighting and averaging said pilot symbols; and

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols during each data symbol interval,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claim 19. (Currently Amended) [[The]] A channel estimation device as claimed in claim 18 for calculating a channel estimation value of data symbols using pilot symbols in a channel in which said data symbols and said pilot symbols are time multiplexed, said channel estimation device comprising:

weighting factor generating means for dividing data symbols in a slot of said channel in a plurality of data symbol intervals, selecting pilot symbols suitable for calculation of a channel estimation value of data symbols during each data symbol interval and generating weighting factors for weighting and averaging said pilot symbols; and

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols during each data symbol interval,

wherein in order to calculate the channel estimation value of the data symbols in the last data symbol section in the i -th (i : integer) slot and to calculate the channel estimation value of the data symbols of the first data symbol section in the $(i+1)$ -th slot, said weighting factor generating means selects the same pilot symbol and generates the weighting factors to be used for weighting and averaging said pilot symbols.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 20. (Previously Presented) The channel estimation device as claimed in claim 18, wherein said weighting factor generating means generates the weighting factors to be used for weighting and averaging mean values of the pilot symbols for each of the plurality of slots of said channel, and said channel estimation value calculating means takes weighted average of the mean values of said pilot symbols using said weighting factors and calculates the channel estimation value of the data symbols in each of the data symbol sections.

Claim 21. (Cancelled).

Claim 22. (Currently Amended) The channel estimation device as claimed in any one of claims claim 18, further comprising:

fading frequency decision means for deciding the fading frequency based on the inner product value of said pilot symbols; and

factor altering means for altering the factors to be used for taking said weighted averaging according to the fading frequency decided by said fading frequency decision means.

Claim 23. (Currently Amended) A demodulation device comprising:

weighting factor generating means for dividing data symbols in the slots of a channel into which the data symbols and pilot symbols are time multiplexed into a plurality of data symbol sections, selecting pilot symbols appropriate for calculating the channel estimation value of the data symbols in each of the data symbol sections, and generating the weighting factors to be used for weighting and averaging said pilot symbols;

Application No. 09/101,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating the channel estimation value of the data symbols in each of data symbol sections; and

channel variation compensating means for compensating channel variation of said data symbols using the channel estimation value calculated by said channel estimation value calculating means,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claims 24-32. (Cancelled).

Claim 33. (Currently Amended) A channel estimation device that calculates a channel estimation value of data symbols of a data channel using pilot symbols of a pilot channel which is parallel multiplexed with said data channel, said channel estimation device comprising:

weighting factor generating means for dividing data symbols in said channel into a plurality of data symbol intervals, selecting pilot symbols suitable for calculation of a channel estimation value of data symbols during each data symbol interval and generating weighting factors for weighting and averaging said pilot symbols; and

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols during each data symbol interval,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 34. (Original) The channel estimation device as claimed in claim 33, wherein said weighting factor generating means generates the weighting factors to be used for weighting and averaging mean values of the pilot symbols in each of a plurality of sections in said pilot channel, and said channel estimation value calculating means takes weighted average of the mean values of said pilot symbols using said weighting factors and calculates the channel estimation value of the data symbols in each of the data symbol sections.

Claim 35. (Previously Presented) The channel estimation device as claimed in claim 33, further comprising:

fading frequency decision means for deciding the fading frequency based on the inner product value of said pilot symbols; and

factor altering means for altering the factors to be used for taking said weighted average according to the fading frequency decided by said fading frequency decision means.

Claim 36. (Currently Amended) The channel estimation device as claimed in any one of claims claim 33, wherein a transmission rate of said data channel differs from the transmission rate of said pilot channel.

Claim 37. (Currently Amended) A demodulation device comprising:

weighting factor generating means for dividing data symbols of a data channel into a plurality of data symbol sections, selecting pilot symbols of a pilot channel that was parallel multiplexed together with said data channel, appropriate for calculating the channel estimation

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

value of the data symbols in each of the data symbol sections, and generating weighting factors to be used for weighting and averaging the pilot symbols;

channel estimation value calculating means for weighting and averaging said pilot symbols using said weighting factors and calculating the channel estimation value of the data symbols of each of the data symbol sections; and

channel variation compensating means for compensating the channel variation of said data symbols using the channel estimation value calculated by said channel estimation value calculating means,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claims 38-46. (Cancelled).

Claim 47. (Currently Amended) A method for estimating a channel, comprising the steps of:

generating weighting factors to be used for weighting and averaging pilot symbols being time multiplexed in a control channel that was parallel multiplexed together with a data channel; and

averaging said pilot symbols using said weighting factors and calculating a channel estimation value of data symbols of said data channel,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 48. (Cancelled).

Claim 49. (Currently Amended) A channel estimation method for calculating a channel estimation value of data symbols using pilot symbols in a channel in which said data symbols and pilot symbols are time multiplexed, comprising the steps of:

dividing the data symbols in the slots of said channel into a plurality of data symbol sections, selecting the pilot symbols appropriate for acquiring the channel estimation value of the data symbols in each of the data symbol sections, and generating weighting factors to be used for weighting and averaging the pilot symbols; and

weighting and averaging said pilot symbols using said weighting factors and calculating the channel estimation value of the data symbols in each of the data symbol sections,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claim 50. (Cancelled).

Claim 51. (Currently Amended) A channel estimation method for calculating a channel estimation value of data symbols of a data channel using pilot symbols of a pilot channel that was parallel multiplexed together with said data channel, comprising the steps of:

dividing the data symbols of said data channel into a plurality of data symbol sections, selecting pilot symbols appropriate for calculating the channel estimation value of the data symbols in each of the data symbol sections, and generating weighting factors to be used for weighting and averaging the pilot symbols; and

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

weighting and averaging said pilot symbols using said weighting factors and calculating the channel estimation value of the data symbols in each of the data symbol sections,

wherein said weighting factors are determined according to the positions of said pilot symbols in the slots of said control channel.

Claim 52. (Cancelled).

Claim 53. (Original) A demodulation device comprising:

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination.

Claim 54. (Original) A demodulation device comprising:

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signal in time using N in number of weighted sequences for data sequences of predetermined frame number;

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

compensating means for compensating data sequence using said respective channel estimation values;

RAKE combining means for RAKE combining of said N data sequences after compensation; and

reliability judgment means for selecting N' (N': natural number, $N' < N$) in number of weighting sequences from said N data sequence after RAKE combining and selecting one data sequence having the highest reliability from N data sequences,

selection of said N' weighting sequences being performed per a predetermined period, for remaining data sequences until performing said reliability judgment again said channel estimation means deriving N' channel estimation value by weighted averaging in time using N' weighting sequences, said compensating means compensating data sequences using N' channel estimation values, said RAKE combining means RAKE combining respective of N' data sequences after compensation, and said reliability judgment means selecting one data sequence having the highest reliability from said N' data sequences.

Claim 55. (Currently Amended) ~~[[The]]~~ A demodulation device as claimed in claim 53 or 54 comprising:

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of said data sequence comprises:

error-correction decoding means for performing error-correction decoding of the data sequence after said RAKE combination;

CRC (Cyclic Redundancy Check) bit extracting means for extracting CRC bits added to said data sequence;

CRC decoding means for decoding the CRC for said data sequence;

frame error detecting means for detecting the presence or absence of a frame error based on a decoding result of said CRC;

number-of-frame-error counting means for counting said number of the frame errors in a previously-determined measuring time; and

weight sequence and data selecting means for selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said counting result of the frame errors.

Claim 56. (Currently Amended) [[The]] A demodulation device as claimed in claim 53 or 54 comprising:

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises:

error-correction decoding means for performing error-correction decoding of the data sequence after said RAKE combination;

likelihood information extracting means for extracting likelihood information that is calculated when performing the error-correction decoding of each of the data sequences;

likelihood averaging means for averaging said extracted likelihood information for a previously-determined measuring time; and

weight sequence and data selecting means for selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said averaged likelihood information.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 57. (Currently Amended) ~~[[The]]~~ A demodulation device as claimed in claim 53 or 54 comprising:

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises:

electric power calculating means for calculating electric power of each of the data sequences after said RAKE combination;

electric power averaging means for averaging said calculation result of the electric power for a previously-determined measuring time; and

weight sequence and data selecting means for selecting the weight sequence having high reliability and data sequence that is demodulated using the weight sequence so selected based on said averaged electric power.

Claim 58. (Currently Amended) ~~[[The]]~~ A demodulation device as claimed in claim 53 or 54 comprising:

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises;

signal-to-noise ratio(ratio of a signal power to a noise power) calculating means for calculating a signal-to-noise ratio of each of the data sequences after said RAKE combination;

signal-to-noise ratio averaging means for averaging the calculation result of said signal-to-noise ratio for a previously-determined measuring time; and

weight sequence and data selecting means for selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said averaged signal-to-noise ratio.

Claim 59. (Currently Amended) ~~[[The]] A demodulation device as claimed in claim 53 or 54 comprising:~~

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises:

error-correction decoding means for performing error-correction decoding of the data sequence after said RAKE combination;

CRC bit extracting means for extracting CRC bits added to said data sequence;

CRC decoding means for decoding the CRC for said data sequence;

frame error detecting means for detecting the presence or absence of a frame error based on a decoding result of said CRC;

number-of-frame-error counting means for counting the number of said frame errors in a previously-determined measuring time;

likelihood information extracting means for extracting likelihood information that is calculated when performing error-correction decoding of each of the data sequences;

likelihood averaging means for averaging said extracted likelihood information for a previously-determined measuring time; and

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

weight sequence and data selecting means for selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said counted number of frame errors of the plurality of data sequences and said averaged likelihood information.

Claim 60. (Currently Amended) ~~[[The]]~~ A demodulation device as claimed in claim 53 or 54 comprising:

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises:

error-correction decoding means for performing error-correction decoding of the data sequence after said RAKE combination;

CRC bit extracting means for extracting CRC bits added to said data sequence;

CRC decoding means for decoding the CRC for said data sequence;

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

frame error detecting means for detecting the presence or absence of a frame error based on a decoding result of said CRC;

number-of-frame-error counting means for counting said number of the frame errors in a previously-determined measuring time;

electric power calculating means for calculating electric power of each of the data sequences after said RAKE combination;

electric power averaging means for averaging said calculation result of the electric power for a previously-determined measuring time; and

weight sequence and data selecting means for selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said number of frame errors and said averaged electric power.

Claim 61. (Currently Amended) ~~[[The]] A demodulation device as claimed in claim 53 or 54 comprising:~~

channel estimating means for deriving N (N is natural number greater than or equal to two) in number of channel estimation values by weighted averaging of pilot signals in time using N in number of weighted sequences;

compensating means for compensating data sequences using said respective channel estimation values;

RAKE combining means for RAKE combining respective of said N data sequences after compensation; and

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

reliability judgment means for selecting one data sequence having highest reliability from said N data sequences after RAKE combination,

wherein said reliability judging means for judging reliability of the data sequence comprises:

error-correction decoding means for performing error-correction decoding of the data sequence after said RAKE combination;

CRC bit extracting means for extracting CRC bits added to said data sequence;

CRC decoding means for decoding the CRC for said data sequence;

frame error detecting means for detecting the presence or absence of a frame error based on a decoding result of said CRC;

number-of-frame-error counting means for counting said number of the frame errors in a previously-determined measuring time;

signal-to-noise ratio calculating means for calculating a signal-to-noise ratio (ratio of a signal power to a noise power) of each of the data sequences after said RAKE combination;

signal-to-noise ratio averaging means for averaging the calculation result of said signal-to-noise ratio for a previously-determined measuring time; and

weight sequence and data selecting means for selecting weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said number of frame errors and said averaged signal-to-noise ratio.

Claim 62. (Original) A demodulation device comprising:

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

channel estimating means for weighted averaging of reception pilot signal using a plurality of weighting sequences and deriving a plurality of channel estimation values;

demodulating means for inputting data sequences and outputting a plurality of demodulated data sequences using said plurality of channel estimation values; and

reliability judging means for selecting one demodulated data by making judgment of reliability of said plurality of demodulated data sequences.

Claim 63. (Original) The demodulation device as claimed in claim 62, wherein said reliability judging means comprises selecting means for selecting predetermined number of the weight sequences from among said plurality of weight sequences based on a judgment result of reliability of said plurality of demodulated data sequences, and

said demodulating means performs the demodulation using only said predetermined number of the weight sequences, when said predetermined number of the weight sequences were selected.

Claim 64. (Previously Presented) The demodulation device as claimed in any one of claims 53, 54 or 62, wherein said pilot signals are time multiplexed in a control channel that was parallel multiplexed together with a data channel in which said data sequence is contained.

Claim 65. (Previously Presented) The demodulation device as claimed in any one of claims 53, 54 or 62, wherein said pilot signals are time multiplexed in one channel together with said data sequence.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 66. (Original) The demodulation device as described in claim 65, wherein said channel estimating means divides the data sequence in the slots of said channel into a plurality of data sequence sections, selects pilot signals appropriate for calculating the channel estimation value of the data in each of the data sequence sections, and calculates the channel estimation value of the data of each of the data sequence sections by weighting and averaging the selected pilot signals.

Claim 67. (Previously Presented) The demodulation device as claimed in any one of claims 53, 54 or 62, wherein said pilot signals are contained in a pilot channel that was parallel multiplexed together with the data channel containing said data sequence.

Claim 68. (Original) The demodulation device as claimed in claim 67, wherein said channel estimating means divides said data sequence into a plurality of data sequence sections, selects pilot signals appropriate for calculating the channel estimation value of the data in each of the data sequence sections, and calculates the channel estimation value of the data in each of the data sequence sections by weighting and averaging the selected pilot signals.

Claim 69. (Original) A demodulation method comprising:
the step of obtaining N pieces of channel estimation values by time-weighting and averaging the pilot signals using N (N: natural number greater than or equal to 2) sets of weight sequences;

the step of compensating data sequence using each of said channel estimation values;

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

the step of RAKE combining each of the N sets of the data sequences after said compensation; and

the reliability judgment step of selecting one set of the data sequences having the highest reliability from among the N sets of the data sequences after said RAKE combination.

Claim 70. (Original) A demodulation method comprising:

the step of obtaining N (N: natural number greater than or equal to 2) pieces of channel estimation values by time-weighting and averaging pilot signals using N sets of weight sequences with respect to a previously-determined number of frames of data sequence;

the step of compensating the data sequence using each of said channel estimation values;

the step of RAKE combining each of N sets of the data sequences after said compensation; and

the reliability judgment step of selecting N' (N': natural number, $N' < N$) sets of the weight sequences having high reliability from among said N sets of the data sequences after said RAKE combination and selecting one set of data sequence having the highest reliability from among the N sets of the data sequences after said RAKE combination,

wherein the selection of said N' sets of the weight sequences is conducted at regular intervals, and throughout a period up to a time when said judgment of reliability is made next time, with respect to remaining part of the data sequence, in said step of estimating the channel, N' pieces of the channel estimation values are obtained by time-weighting and averaging the data sequence using the N' sets of the weight sequences; in said step of compensating, the data sequence is compensated using the N' pieces of the channel estimation values; in said step of the RAKE combination, each of the N' sets of the data sequences after the compensation is RAKE

Application No. 02/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

combined; and in said reliability judgment step, one set of the data sequence having the highest reliability is selected from among the N' sets of the data sequences.

Claim 71. (Original) The demodulation method as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

- error-correction decoding the data sequence after said RAKE combination;
- extracting CRC bits added to said data sequence;
- decoding the CRC with respect to said data sequence;
- detecting the presence or absence of a frame error based on said demodulation result of the CRC;
- counting the number of said frame errors in a previously-determined measuring time; and
- selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said counting result of the frame errors.

Claim 72. (Original) The demodulation method as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

- error-correction decoding the data sequence after said RAKE combination;
- extracting likelihood information calculated when performing error-correction decoding of each of the data sequence;
- averaging said extracted likelihood information for a previously-determined measuring time; and

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said averaged likelihood information.

Claim 73. (Original) The demodulation method as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

calculating electric power of each of the data sequences after said RAKE combination;
averaging the calculation result of said electric power for a previously-determined measuring time; and

selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said averaged electric power.

Claim 74. (Original) The demodulation method as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

calculating a signal-to-noise ratio of each of the data sequences after said RAKE combination;

averaging the calculation result of said signal-to-noise ratios for a previously-determined measuring time; and

selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said averaged signal-to-noise ratio.

Claim 75. (Original) The demodulation method as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

performing error-correction decoding of the data sequences after said RAKE combination;

extracting CRC bits added to said data sequence;

decoding the CRC with respect to said data sequence;

detecting the presence or absence of a frame error based on said decoding result of the CRC;

counting said number of the frame errors in a previously-determined measuring time;

extracting likelihood information that is calculated when performing error-correction decoding of each of the data sequences;

averaging said extracted likelihood information for a previously-determined measuring time; and

selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said measured number of the frame errors of the plurality of the data sequences and said averaged likelihood information.

Claim 76. (Original) The demodulation method as claimed in either of claim 69 or 70, wherein said reliability judgment step comprises the steps of:

error-correction decoding said data sequences after said RAKE combination;

extracting CRC bits added to said data sequence;

decoding the CRC with respect to said data sequence;

detecting the presence or absence of a frame error based on the decoding result of said CRC;

counting the number of said frame errors in a previously-determined measuring time;

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

calculating electric power of each of received data sequences after said RAKE combination;

averaging the calculation result of said electric power for a previously-determined measuring time; and

selecting the weight sequence having high reliability and the data sequence that is demodulated using the weight sequence so selected based on said number of frame errors and said averaged electric power.

Claim 77. (Original) The demodulation method of as claimed in claim 69 or 70, wherein said reliability judgment step comprises the steps of:

error-correction decoding said data sequences after said RAKE combination;

extracting CRC bits added to said data sequence;

decoding the CRC with respect to said data sequence;

detecting the presence or absence of a frame error based on the decoding result of said CRC;

counting the number of said frame errors in a previously-determined measuring time;

calculating a signal-to-noise ratio of each of the data sequences after said RAKE combination;

averaging calculation result of said signal-to-noise ratios for a previously-determined measuring time; and

selecting the weight sequence having a high reliability and the data sequence that is demodulated with the weight sequence so selected based on the number of said frame errors and said averaged signal-to-noise ratio.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 78. (Original) A demodulation method comprising the steps of:
weighting and averaging pilot signals using a plurality of weight sequences to obtain a plurality of channel estimation values;
deriving a plurality of demodulated data sequences from a data sequence using said plurality of channel estimation values; and
selecting one output data sequence by making judgment of reliability of said plurality of demodulated data.

Claim 79. (Original) The demodulation method as claimed in claim 78, wherein, based on the judgment result of reliability of said plurality of demodulated data sequences, a predetermined number of weight sequences are selected from among said plurality of weight sequences, and after the selection, demodulation through the use of only the selected weight sequences is performed.

Claim 80. (Previously Presented) The demodulation method as claimed in any one of claims 69, 70 or 78, wherein said pilot signals are time multiplexed into a control channel that is parallel multiplexed together with the data channel in which said data sequence is contained.

Claim 81. (Previously Presented) The demodulation method as claimed in any one of claims 69, 70 or 78, wherein said pilot signals are time multiplexed into one channel together with said data sequence.

Application No. 09/701,705
Amendment "A" dated November 18, 2005
Reply to Office Action mailed August 30, 2005

Claim 82. (Original) The demodulation method as claimed in claim 81, wherein said step of estimating a channel divides said data sequence in the slots of said channel into a plurality of data sequence sections, selects pilot signals appropriate for calculating the channel estimation value of the data of each of the data sequence sections, and calculates a channel estimation value of the data of each of the data sequence sections by weighting and averaging the selected pilot signals.

Claim 83. (Previously Presented) The demodulation method as claimed in any one of claims 69, 70 or 78, wherein said pilot signals are contained in a pilot channel that was parallel multiplexed together with the data channel containing said data sequence.

Claim 84. (Original) The demodulation method as claimed in claim 83, wherein said step of estimating a channel divides said data sequence into a plurality of data sequence sections, selects pilot signals appropriate for calculating the channel estimation value of the data in each of the data sequence sections, and calculates the channel estimation value of the data of each of the data sequence sections by weighting and averaging the selected pilot signals.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.